



MINI EXCAVATORS

& COMPACT EQUIPMENT

0.75 – 2.0 Tons

EPA / CE / EURO V Certified

Kubota · Yanmar · B&S · KOOP



TIANJIN WANJI IMP. & EXP. TRADING CO., LTD.

ABOUT WANJI

Tianjin Wanji Imp. & Exp. Trading Co., Ltd. is a professional import and export trading company specializing in compact construction equipment. Our team has deep roots in the Jining machinery manufacturing cluster — China's premier hub for mini excavator production — with long-standing partnerships with leading factories in the region.

We offer a comprehensive range of mini excavators from 0.75 to 2.0 tons, including diesel and electric models, with a full suite of attachments. All products are available with EPA, CE, and EURO 5 certified engines from internationally recognized brands including Kubota, Yanmar, Briggs & Stratton, and KOOP.

Our cooperation models include:

Model A — Direct Import & Export Trade

Factory-direct pricing, full export documentation, FOB/CIF/DDP terms, flexible MOQ from 1 unit.

Model B — OEM / Private Label

Custom branding, color schemes, and decals. Your logo on every machine — built to your specifications.

WJ10

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.025m ³
Operating Weight	1050kg
Engine Model	Koop,B&S,Kubota
Fuel Tank Capacity	10L
Travel Speed	1.5km/h
Swing Speed	10r/min
Max. Climbing Degree	58°
Bucket Digging Force	9.2KN
Largest Traction	13KN
Overall Length	2880mm
Overall Width	950mm
Overall Height	2265mm
Min. Ground Clearance	80mm

Track Length	1393mm
Track Width	950mm
Turntable Width	820mm
Max.Digging Height	2771mm
Max.Dumping Height	1917mm
Max.Digging Depth	1593mm
Max. Digging Reach	3189mm
Min. Swing Radius	1387mm
Track Gauge	640-840mm
Height Of Counterweight	480mm
Deflection Angle Left/Right	56°/57°
Maximum dozing height/depth	185/226mm
Working pressure	17.5Mpa

PRODUCT DETAIL

1

Convenient inspection and maintenance. Three cast iron counterweights to ensure balance during work

3

The newly upgraded three-way stop valve can use hydraulic thumb clamps and hydraulic quick changes at the same time.

5

Standard big arm side swing function, cast iron side swing head, beautiful and durable

2

The bulldozer cylinder is equipped with a protective plate to protect the cylinder from damage during operation

4

Plunger motor, two-speed travel, the motor has a protective shell, the travel speed is 2.3Km-4.6Km/h

6

Convenient travel, dozer blade and chassis telescopic control joystick

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ12C

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.025m ³
Operating Weight	1250kg
Engine Model	Kubota Z482
Fuel Tank Capacity	15L
Travel Speed	1.8-4.0km/h
Swing Speed	12r/min
Max. Climbing Degree	58°
Bucket Digging Force	12.5KN
Largest Traction	19KN
Overall Length	2880mm
Overall Width	820-1020mm
Overall Height	2265mm
Min. Ground Clearance	80mm

Track Length	1393mm
Track Width	820-1020mm
Turntable Width	820mm
Max.Digging Height	2771mm
Max.Dumping Height	1917mm
Max.Digging Depth	1593mm
Max. Digging Reach	3189mm
Min. Swing Radius	1387mm
Track Gauge	640-840mm
Height Of Counterweight	480mm
Deflection Angle Left/Right	56°/57°
Maximum dozing height/depth	185/226mm
Working pressure	19.5Mpa

PRODUCT DETAIL

1

Convenient inspection and maintenance. Three cast iron counterweights to ensure balance during work.

3

The newly upgraded three-way stop valve can use hydraulic thumb clamps and hydraulic quick changes at the same time.

5

Standard big arm side swing function, cast iron side swing head, beautiful and durable

2

Standard big arm side swing function, cast iron side swing head, beautiful and durable

4

Plunger motor, two-speed travel, the motor has a protective shell, the travel speed is 2.3Km-4.6Km/h

6

Convenient travel, dozer blade and chassis telescopic control joystick

WJ08

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.02m³
Chassis Width	730mm
Track Length	1100mm
Gradeability	40°
Chassis Ground Clearance	385mm
Track Width	150mm
Volume of fuel tank	3.5L
Overall Dimension	2000*730*1880mm
Transport Length	2200mm
Excavator Height	1880mm
Hydraulic flow	40L/Min
Hydraulic tank capacity	16L
Working pressure	16Mpa

Engine	KOOP 192F Diesel Engine (Euro 5)
Engine Power	7.0kw
EPA Engine Optional	Briggs&Stratton gasoline /13.5hp
Max.Digging Height	2500mm
Max.Dumping Height	1600mm
Max.Digging Depth	850mm
Max.Digging Radius	2478mm
Turning Radius	1360mm
Bucket excavating force	11KN
Operating Weight	750kg
Configuration	Valve:Beifang Brand; Pump:Xingzou Brand; Load sensitive system

PRODUCT DETAIL

1

Koop 192F diesel engine and B&S gasoline engine

3

The pin comes with grease fitting,more lubricating

5

Strong cylinder, imported seals, good flexibility, longer use time

2

Double hand front operation system,easy to operate

4

The bulldozer blade is widened and thickened,durable

6

I-shaped industrial chassis, engineering rubber track, can be used in all terrain

WJ09

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.02m³
Chassis Width	730mm
Track Length	1100mm
Gradeability	40°
Chassis Ground Clearance	385mm
Track Width	150mm
Volume of fuel tank	3.5L
Overall Dimension	2000*730*1880mm
Transport Length	2200mm
Excavator Height	1880mm
Hydraulic flow	40L/Min
Hydraulic tank capacity	16L
Working pressure	16Mpa

Engine	KOOP 192F Diesel Engine (Euro 5)
Engine Power	7.0kw
EPA Engine Optional	Briggs&Stratton gasoline /13.5hp
Max.Digging Height	2500mm
Max.Dumping Height	1780mm
Max.Digging Depth	840mm
Max.Digging Radius	2500mm
Turning Radius	1100mm
Bucket excavating force	11KN
Operating Weight	800kg
Configuration	Valve:Beifang Brand; Pump:Xingzou Brand; Load sensitive system

PRODUCT DETAIL

- 1 Koop 192F diesel engine and B&S gasoline engine
- 2 Double hand front operation system,easy to operate
- 3 The pin comes with grease fitting,more lubricating
- 4 The bulldozer blade is widened and thickened,durable
- 5 No tail design
- 6 Small size, strong power, multi-functional excavator, big arm can be recycled to the shortest, easy to enter the elevator

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ12D

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.02m³
Operating Weight	1035kg
Engine Model	Kubota D722
Fuel Tank Capacity	15L
Travel Speed	2.1-4.0km/h
Swing Speed	13r/min
Max. Climbing Degree	30°
Bucket Digging Force	6.5KN
Largest Traction	19KN
Overall Length	3005mm
Overall Width	750-950mm
Overall Height	2160mm
Min. Ground Clearance	140mm

Track Length	1393mm
Track Width	750-950mm
Turntable Width	725mm
Max.Digging Height	3060mm
Max.Dumping Height	2150mm
Max.Digging Depth	1550mm
Max. Digging Reach	3350mm
Min. Swing Radius	1445mm
Track Gauge	580-780mm
Height Of Counterweight	380mm
Deflection Angle Left/Right	54°/59°
Maximum dozing height/depth	195/140mm
Working pressure	16Mpa

PRODUCT DETAIL

1

Three cast iron counterweights to ensure balance during work

3

Convenient travel, dozer blade and chassis telescopic control joystick

5

Standard structure telescopic function, telescopic range 750-950mm, 180mm wide engineering track.

2

The armrest box has a height-adjustable armrest support, which has excellent ergonomics and is suitable for different drivers.

4

Standard big arm side swing function, cast iron side swing head, beautiful and durable

6

The newly upgraded three-way stop valve can use hydraulic thumb clamps and hydraulic quick changes at the same time.

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ12A

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.025m ³
Chassis Width	930mm
Track Length	1250mm
Gradeability	40°
Chassis Ground Clearance	385mm
Track Width	180mm
Volume of fuel tank	3.5L
Overall Dimension	2200*930*2200mm
Transport Length	2200mm
Excavator Height	2200mm
Hydraulic flow	40L/Min
Hydraulic tank capacity	16L
Working pressure	16Mpa

Engine	KOOP 192F Diesel Engine (Euro 5)
Engine Power	7.0kw
EPA Engine Optional	Briggs&Stratton gasoline /13.5hp
Max.Digging Height	2550mm
Max.Dumping Height	1850mm
Max.Digging Depth	1650mm
Max.Digging Radius	2400mm
Turning Radius	1190mm
Bucket excavating force	11KN
Operating Weight	1000kg
Configuration	Valve:Beifang Brand; Pump:Xingzou Brand; Double Gear Pump

PRODUCT DETAIL

1

Koop 192F diesel engine and B&S gasoline engine

3

The pin comes with grease fitting,more lubricating

5

Timer and voltmeter

2

The bulldozer blade is widened and thickened,durable

4

Adjustable track operational

6

Swing boom optional

WJ13

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.025m ³
Chassis Width	980mm
Track Length	1300mm
Gradeability	40°
Chassis Ground Clearance	385mm
Track Width	180mm
Volume of fuel tank	3.5L
Overall Dimension	2200*1100*2200mm
Transport Length	2400mm
Excavator Height	2200mm
Hydraulic flow	40L/Min
Hydraulic tank capacity	16L
Working pressure	16Mpa

Engine	KOOP 192F Diesel Engine (Euro 5)
Engine Power	7.0kw
EPA Engine Optional	Briggs&Stratton gasoline /13.5hp
Max.Digging Height	2550mm
Max.Dumping Height	1710mm
Max.Digging Depth	1740mm
Max.Digging Radius	3100mm
Turning Radius	1635mm
Bucket excavating force	11KN
Operating Weight	1100kg
Configuration	Valve:Beifang Brand; Pump:K.Jun Brand

PRODUCT DETAIL

1

Koop 192F diesel engine and B&S gasoline engine

3

Swing boom optional

5

360 degree rotation

2

Optional telescopic chassis

4

The track length of 41 sections increases the ground contact area and makes walking more stable. Tailless swing, flexible and convenient

6

Hammer cut-off valve,durable and wear-resistant cast steel material,good mechanical performance,prevent oil dripping and leakage

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ18

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.03m³
Chassis Width	1100mm
Track Length	1030mm
Gradeability	20°
Chassis Ground Clearance	385mm
Track Width	180mm
Volume of fuel tank	10L
Overall Dimension	2200*1100*2200mm
Transport Length	2200mm
Excavator Height	2200mm
Hydraulic flow	40L/Min
Hydraulic tank capacity	12L
Working pressure	16Mpa

Engine	Kubota D722 (EURO 5 and EPA emission)
Engine Power	10.2kw
Max.Digging Height	2660mm
Max.Dumping Height	1900mm
Max.Digging Depth	1910mm
Max.Digging Radius	3280mm
Turning Radius	1636mm
Bucket excavating force	15KN
Operating Weight	1200kg
Configuration	Valve:Beifang Brand; Pump:K.Jun Brand; Double Gear Pump

PRODUCT DETAIL

- 1

Kubota diesel engine,international famous brand ,quality assurance.
- 2

Hydraulic Pilot Operate,easy to operate
- 3

Swing Boom optional
- 4

No Tail design,flexible operation
- 5

The bulldozer blade is widened and thickened,durable
- 6

Operation lever, simple and flexible, easy to operate

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ20

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.03m³
Chassis Width	1160mm
Track Length	1250mm
Gradeability	40°
Chassis Ground Clearance	385mm
Track Width	230mm
Volume of fuel tank	15L
Overall Dimension	2200*1100*2200mm
Transport Length	2200mm
Excavator Height	2200mm
Hydraulic flow	40L/Min
Hydraulic tank capacity	16L
Working pressure	16Mpa

Engine	Kubota D722 (EURO 5 and EPA emission)
Engine Power	10.3kw
Max.Digging Height	2700mm
Max.Dumping Height	1900mm
Max.Digging Depth	1910mm
Max.Digging Radius	3280mm
Turning Radius	1636mm
Bucket excavating force	15KN
Operating Weight	1500kg
Configuration	Valve:Taifung Brand; Pump:Taifung Brand; Double Gear Pump

PRODUCT DETAIL

- 1 Adopt Kubota diesel engine,international famous brand ,quality assurance.
- 2 Double row bead rotating support, fast speed, high efficiency, more flexible, and more stable
- 3 Noiseless, high efficiency, stable work, easy to operate
- 4 Electric control handle operation, simple structure, long service life
- 5 Full wrapped high and low speed motor, protecting the walking motor from damage and providing longer lifespan
- 6 Three sided opening for more convenient maintenance and upkeep

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ22

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Engine	Kubota D902/Laidong 380
Operating weight	1850KG
Bucket capacity	0.04m³
Rated power	11.8kw/18.1kw
Hydraulic pump model	piston pump
Max.flow	38L/min
Working pressure	19.5Mpa
Hydraulic oil tank capacity	20L
Travel speed	1.8-4.0km/h
Swing speed	12r/min
Max. climbing degree	58%
Overall length	2880mm
Overall width	980-1280mm

Track ground length	1250mm
Track length	1393mm
Track width	980-1280mm
Max. digging height	2771mm
Max. dumping height	1917mm
Max. digging depth	2324mm
Max. vertical wall digging depth	2300mm
Max. digging reach	3189mm
Min. swing radius	1387mm
Maximum dozing height/depth	185/226mm

PRODUCT DETAIL

- 1 Hydraulic safety lock to ensure safe operation.Large tilt angle makes it easier to get on and off the vehicle
- 2 Electronically controlled hydraulic pilot handle,which can control chassis telescopic and electronic horn
- 3 Standard big arm side swing function, cast iron side swing head, beautiful and durable
- 4 The instrument panel display screen can display working hours, fuel volume, water temperature, making it easy to observe the health of the machine
- 5 The front windshield of the driver's cab can be folded upwards
- 6 Plunger motor, two-speed travel, the motor has a protective shell, the travel speed is 2.3Km-4.6Km/h

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

WJ-E12

MINI EXCAVATOR



PRODUCT INFORMATION

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO.,LTD

ISO CE EPA EURO 5

Bucket Capacity	0.025m³
Chassis Width	930mm
Track Length	1250mm
Gradeability	40°
Chassis Ground Clearance	385mm
Track Width	180mm
Overall Dimension	2200*930*2200mm
Transport Length	2200mm
Excavator Height	2200mm
Battery Capacity	126Ah
Battery Voltage	72V
Charging Time	6H-8H
Decibels within 1 meter	<55

Engine	Lithium Battery
Motor Power	4KW
Power consumption per hour	1KW/h
Max.Digging Height	2550mm
Max.Dumping Height	1850mm
Max.Digging Depth	1650mm
Turning Radius	1190mm
Bucket excavating force	11KN
Operating Weight	1000kg
Configuration	Valve:Beifang Brand; Pump:Xingzou Brand; Double Gear Pump

PRODUCT DETAIL

- 1

High energy density, long cycle life, safe to use
- 2

Self-contained counterweight, increase the weight of the body and improve the stability of the vehicle
- 3

The pin comes with grease fitting,more lubricating
- 4

The bulldozer blade is widened and thickened,durable
- 5

Timer and voltmeter
- 6

Hammer cut-off valve,durable and wear-resistant cast steel material,good mechanical performance,prevent oil dripping and leakage

ACCESSORIES

One Machine, Multi-usage • Quick and easy replacement of accessories

1 	2 	3 	4 
200 Bucket	400 Bucket	500/600/800/1000mm plain B..	600/800mm Tilting Bucket
5 	6 	7 	8 
Shell Bucket	Sieve Bucket	Snow Shovel	V Ditch Bucket
9 	10 	11 	12 
Rotary Bucket	Tilt Rotary Hitch	Mechanical Quick Hitch	Automatic Quick Hitch

13



360° Swing Grab

14



Wood Grabber

15



Trailer

16



Trailer2

17



Trailer3

18



Thumb

19



Thumb Bucket

20



Hydraulic Thumb

21



Double Hook Ripper

22



Ripper

23



Auger Drill

24



Hydraulic Hammer

25



Wood Chopping Machine

26



Cone Log Splitter

27



Ditcher

28



Milling head

29



Rock Saw

30



Rake

31



Plate Compactor

32




Pallet Fork

33



Ramps

34



Snow Plow

35



Sweeper

36



Snow Blower

WANJI

TIANJIN WANJI IMP. & EXP. TRADING CO., LTD.

Compact Construction Equipment — Mini Excavators & Attachments

Email: info@wanji-imp.com

Web: www.wanji-imp.com

Manufacturing Base: Jining, Shandong, China

Export Office: Tianjin, China